

What is claimed is:

1. A method for optimal multimedia content delivery over networks from server to client comprising the steps of:
- Delineating a state variable that represents the data rate to each client;
- Delineating a set of requirements which represent the time-varying constraints on the data rate of said multimedia content; given by:
- (1) The total data rate for all clients does not exceed the maximum throughput of the server or network, whichever is least;
 - (2) The data rate from server to client does not exceed the maximum data rate for the client;
 - (3) The data rate to the client will never overflow the client buffer
 - (4) The server will never underflow
 - (6) The data rate from the server will never be less than the client's minimum data rate, which is a non-increasing function of time obtained by dividing the content not yet delivered by the remaining play time
- Delineating a cost function which represents the value of a proposed solution
- Performing periodic computations to solve said inequalities to obtain the state value that maximizes said cost function.
2. A method as in claim 1 further comprising:
- said requirements further comprise:
- The current maximum client data rate is given by the minimum of:
- The stored initial maximum client data rate;
 - The data rate required to fill the remaining client buffer during the current of said periodic computations;
 - The data rate required to complete the delivery of said multimedia content.
 - The client data rate never exceeds said current maximum client data rate
- Whereby said current maximum client data rate is periodically recomputed to maintain an optimal solution over a give period of time.
3. A method as in claim 2 further comprising:
- Said cost function represents maximal throughput and is given by the sum of said client data rates for all active clients.
4. A method as in claim 2 further comprising:
- Said cost function represents maximal charge and is given by the sum for all active clients of: said client data rates times the client's cost of service..

5. A method as in claim 3 for bandwidth allocation for delivery of multimedia data from server to one or more clients over a network, comprising the steps of:

Determining the maximum flow rate and minimum flow rate for each client;
Determining the flow rate range for each client as given by the difference between said maximum flow rate and said minimum flow rate;
Initializing current flow rate for each client as said minimum flow rate and summing said flow rate into total server flow rate; and
Allocating remaining server bandwidth to remaining clients until they each saturate or no bandwidth remains.

6. A method as in claim 5 wherein said step of allocating remaining server bandwidth to remaining clients is done fairly by a procedure that comprises the steps of:

Sorting the list of clients according to said flow rate range; and

Determining equally-allocated remaining server bandwidth if allocated evenly to all remaining unprocessed clients and;

Determining the range of remaining client bandwidth as given by the difference between said maximum flow rate and said minimum flow rate;

Determining saturation by comparing said equally-allocated remaining server bandwidth and said range of remaining client bandwidth, and allocating the lesser of these two amounts to each remaining client flow rate;

Whereby allocating flow to remaining clients based upon the sorted client range flow rates and determining allocation of remaining server bandwidth based upon a comparison of saturation of server versus saturation of each client maximizes allocation of total bandwidth for maximal flow rate to maximum number of clients.

7. A method as in claim 4 for bandwidth allocation for delivery of multimedia data from server to one or more clients over a network, comprising the steps of:

Determining the maximum flow rate and minimum flow rate for each client;

Determining the flow rate range for each client as given by the difference between said maximum flow rate and said minimum flow rate;

Sorting the list of clients according to said flow rate range;

Initializing current flow rate for each client as said minimum flow rate and summing said flow rate into total server flow rate;

Allocating remaining server bandwidth to remaining clients such that lower paying clients receive bandwidth only if higher paying ones are saturated.

8. A method as in claim 7 wherein said step of allocating remaining server bandwidth to remaining clients comprises the steps of:

For each remaining unprocessed client:

Determining equally-allocated remaining server bandwidth if allocated evenly to all remaining unprocessed clients and;

Determining the range of remaining client bandwidth as given by the difference between said maximum flow rate and said minimum flow rate;

Determining saturation by comparing said equally-allocated remaining server bandwidth and said range of remaining client bandwidth, and allocating the lesser of these two amounts to each remaining client flow rate;

Whereby allocating flow to remaining clients based upon the sorted client range flow rates and determining allocation of remaining server bandwidth based upon a comparison of saturation of server versus saturation of each client maximizes allocation of total bandwidth for maximal flow rate to maximum number of clients.

9. A method for connection acceptance control for delivery of multimedia data from server to one or more clients over a network, comprising the steps of:

Determining the server swing capacity given by the difference between the total server bandwidth and the sum of the minimum flow rate for each client;

Allocating server bandwidth for each prospective client which will fit without server bandwidth saturation, as determined by comparing the average data play rate of each prospective client with the remaining bandwidth available to the server.

10. A method as in claim 9 wherein said remaining bandwidth available to the server is given by said server swing capacity.

11. A method as in claim 10 wherein said remaining bandwidth available to the server is given by said server swing capacity less a server flow safety margin, thereby allowing server capacity to be subsequently lowered by up to the margin without requiring load shedding, and without affecting client sessions in process.

12. A method as in claim 9 wherein said step of allocating server bandwidth for each prospective client which will fit without server bandwidth saturation is further comprised of:

Allocating server bandwidth to each prospective client sequentially until a prospective client is located in which said average data play rate exceeds said sever swing capacity.

13. A method as in claim 9 wherein said step of allocating server bandwidth for each client which will fit without server bandwidth saturation is further comprised of:

Allocating server bandwidth to each prospective client sequentially for each client which can be activated without server bandwidth saturation.

14. A method for bandwidth allocation for delivery of multimedia data from server to one or more clients over a network, comprising the steps of:

Storing a sequence of data representing scheduled bandwidth changes for the server;
Determining the maximum flow rate and minimum flow rate for each client at the present time;
Determining the flow rate range for each client as given by the difference between said maximum flow rate and said minimum flow rate;
Sorting the list of clients according to said flow rate range;

A'

page 25 of 37